

Latham's Security Doorsets Ltd

TEST REPORT

REPORT NUMBER

180426004SHF-BP-5

ISSUE DATE


2018/10/9

PAGES

7

DOCUMENT CONTROL NUMBER

LFT-APAC-SHF-OP-10a © 2018 INTERTEK





Intertek Testing Services Ltd., Shanghai Plant 5, No. 6958 Daye Road, Fengxian District, Shanghai, China Tel: 021-61136116 Fax: 021-61189921

Website: www.intertek.com

Test Report

Issue Date: 2018/10/9 Intertek Report No. 180426004SHF-BP-5

Applicant: Latham's Security Doorsets Ltd

Applicant Address: No.C29 Export Trade Processing Zone, Economic Exploration Garden, Chongqing

North New District, Chongqing, China

Attn: Ricky

SUBJECT: Performance testing

STEEL DOOR

Dear Sir,

This test report represents the results of our evaluation of the above referenced product(s) to the requirements contained in the following standards:

TEST METHODS AND STANDARDS
Refer to the next following Pages.

SAMPLE ID	MODEL	SPECIFICATION
S180426004SHF.005	BF1/2NN****XA50	2200mm*2200mm

SAMPLE RECEIEVED: 2018/5/29

TESTED FROM: 2018/7/23 TO 2018/10/9

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.



Issue Date: 2018/10/9 Intertek Report No. 180426004SHF-BP-5


Test Items, Method and Results:

Test method: ISO 10140-2:2010

Temperature: 28 °C Relative Humidity: 70 % Volume of the source room: 112 $\,\mathrm{m}^3$ Volume of the receiving room: 137 $\,\mathrm{m}^3$

Specimen area: 4.9 m² (detail drawing see Test Photos)

Frequency	Sound Reduction		
(Hz)	Index, Ri (dB)		
100	21.9		
125	25.8		
160	24.8		
200	28.1		
250	28.2		
315	27.0		
400	28.8		
500	31.8		
630	33.5		
800	35.0		
1000	36.3		
1250	37.0		
1600	37.5		
2000	36.9		
2500	35.8		
3150	32.8		
4000	33.3		
5000	33.7		



Rating according to ISO 717-1:2013

Weighted Sound reduction index	Rw(C;Ctr)=	35 (-1; -3)	dB
Spectrum A-weighted pink noise	C=	-1	dB
Spectrum A-weighted urban traffic noise	Ctr=	-3	dB


Note:

1. Evaluation based on laboratory measurement results obtained by an engineer method.



Issue Date: 2018/10/9 Intertek Report No. 180426004SHF-BP-5


Test Photos:








Issue Date: 2018/10/9 Intertek Report No. 180426004SHF-BP-5

Test Photos:









Sample drawing



Issue Date: 2018/10/9 Intertek Report No. 180426004SHF-BP-5

Test Photos:





Test set up



Issue Date: 2018/10/9 Intertek Report No. 180426004SHF-BP-5

APPENDIX: SAMPLE RECEIVED PHOTO



REPORT AUTHORIZED

When signed with physical or electronic signature, the contents of this report have been prepared and approved per Intertek's quality process in accordance with ISO 17025.

Name: Jodie Zhou

Title: Reviewer

Name Evyn Cui

Title. Project Engineer

Revision:

NO.	DATE	CHANGES	AUTHOR	REVIEWER
180426004SHF-BP-5	2018/10/9	First issue	Evyn Cui	Jodie Zhou