Document Title:

DOP - Double Fire Exit Doorsets

Key Element:

Document ID:

LSSD-4973-016

R&D

DOP CE UKCA

CONSTRUCTION PRODUCTS REGULATION 2011 DECLARATION OF PERFORMANCE

No. 4973-016

Unique identification code of the product-type:

Double Fire Exit Doorset

Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:

351MX, 352MX, 353MX, 354MX

301MX, 302MX, 303MX, 304MX, 305MX, 306MX, 307MX, 308MX, 309MX, 310MX, 311MX, 312MX, 313MX, 314MX

Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

External pedestrian panic/emergency exit doorset

Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

LATHAM'S SECURITY DOORSETS LTD 35-37 HAINGE ROAD **TIVIDALE WEST MIDLANDS B69 2NY UNITED KINGDOM**

Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

N/A

System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

SYSTEM 1

In case of the declaration of performance concerning a construction product covered by a harmonized standard: EN14351-1:2006 + A2:2016

Notified test body: 1121 - ability to release, 1023 - other performance

European Technical Assessment:

9. Declared Performance:

Essential characteristics	Performance	Harmonised technical specification
Watertightness – Non-shielded (A)	2A	
Watertightness – Shielded (B)	NPD	
Dangerous substances	None	
Resistance to wind load – Test pressure	1	
Resistance to wind load – Frame deflection	С	
Ability to release	EN 1125	EN 14351-1:2006+A2:2016
(locked doors in escape routes only)	EN 1935	EN 14331-1.2000+A2.2010
Load bearing capacity of safety devices	NPD	
Height	1979mm - 2054mm	
Acoustic performance	35dB	
Thermal transmittance	2.2 W/m ² ·K	
Air Permeability	Class 3	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A Latham

Name: Alex Latham

Position: Managing Director

Date: 25.08.2023

ISSUE DATE: 30.09.2021 PAGE NO: REVISION NO: APPROVED BY REVISION DATE: ELECTRONIC REF:

A.BRADFORD

(16) DOP - 50mm Security Fire Exit Doorsets CE - Double