

Approved Body No. 1121

Certificate of Constancy of Performance

1121-CPR-UK-MA7853

In compliance with Construction Products Regulation 2011 (retained EU law EUR 2011/305) as amended by the Construction Products (Amendment etc.) (EU Exit) Regulations 2019 and the Construction Products (Amendment etc.) (EU Exit) Regulations 2020, this certificate applies to the Construction Product:

70mm, High Security Fire Exit Door

Product: External Pedestrian Doorsets Covered by EN 14351-1

Intended use: Fire compartmentation and/or escape routes (subject to restrictions in regards opening directions – see below).

Essential characteristics	Performance	Harmonised Technical Specification
Resistance to Fire ¹	E15 / E20 / E30 / E60 / E90 / EW15 / EW20 / EW30 / EW60 / EW90*	EN 16034: 2014
Smoke control (only for applications where limitation of smoke spread is required)	NPD	
Ability to release	NPD	
Self Closing (only for self closing fire resistance and/or smoke control doorsets and/or openable windows) ²	C	
Durability of ability to release	NPD	
Durability of self-closing	NPD	

The following documentation has been used in support of the essential characteristics performance stated above:

1. Classification referenced WF Report No. 534961.
2. Test referenced WF Report No. 503136/R (Doorset A), 503136/R (Doorset B) & Classification referenced WF Report No. 534961.

* It shall be noted that the relative fire resistance classifications applicable to a door opening away from the risk direction may differ to those classifications applicable to a door opening towards the fire risk direction. The classification report, WF No. 534961, shall be consulted for further clarification.

Approved Body No. 1121

Certificate of Constancy of Performance
1121-CPR-UK-MA7853

Placed on the market under the name of

Latham's Security Doorsets Ltd
35/37 Hainge Road,
Tivdale,
Oldbury,
West Midlands,
B69 2NY,
United Kingdom

and produced in the manufacturing plant

CKV13302-1 & CKV13302-3

This is coded format and the information is held by the Approved Body

This certificate attests that all provisions concerning the assessment and verification of constancy of performance and the performances described in Annex ZA of the standard(s)

EN 16034: 2014

Under System 1 for the performance set out in this certificate are applied and that the Factory Production Control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product.

This certificate was first issued on **22/01/2024** and will remain valid until the below date as long as neither the designated standard, the Construction Product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, or unless suspended or withdrawn by the Approved Product Certification Body.

UKCA certificate valid to: **21/01/2027**



0087

Paul Duggan
Certification Manager

Warringtonfire Testing and Certification Limited
Suite 302, The Genesis Centre, Birchwood, Warrington, WA3 7BH, UK